

SAVOX

SAVOX C-C550/M12 Remote Speaker Mic

The SAVOX C-C440 com-control unit is a push-to-talk unit designed for use with your two-way radio in demanding environments. It offers easy and reliable communication for professionals requiring durable equipment when operating in harsh conditions, and is ideal for those who need to communicate hands-free and/or with their radio secured underneath protective clothing. With a headset it provides a hands-free way to stay connected with your team and ensure the efficiency and safety of your operations. Rugged to IP67.

Key benefits

- Dust proof and water submersible (IP67)
- Extra large push-to-talk button
- Excellent tactile feel and operation; suitable for wearing under clothing and with gloves
- Large 360° rotating clip



Market Segment
Size L
Size H
Housing Colour

Public Safety
79 mm
115 mm
Black

Product code
Size W
Housing Material
Weight (text)

L552172-10B1100
37 mm
Fibre-Reinforced Plastic
170 g

Environmental Tests	Blowing Rain MIL810G 506.5, Procedure I, Blowing Sand MIL810G 510.5, Procedure II, Damp heat steady state MIL810G 507.5, Procedure I, Drop MIL810G 516.6, Procedure IV, Dust test MIL810G 510.5, Procedure I, Fluid contamination MIL810G 504.1, Procedure II (occasional contamination), High temperature (operational) MIL810G 502.5, Procedure II, A2, Immersion (IPx7) MIL810G 512.5, Procedure I, Mechanical Shock (Bump) MIL810G 516.6, Procedure I, Mechanical Shock MIL810G 516.6, Procedure I, Salt fog MIL810G 509.5, Solar radiation MIL810G 505.5, Procedure II A2, Thermal shock MIL810G 503.5, Procedure I-A, Vibration MIL810G 514.6, Procedure I, Category 24	Operational Temperature Min	-40 °C (-40 °F)
Operational Temperature Max	85 °C (185 °F)	Ingress Protection	IP66, IP67
Storage Temperature Min	-25 °C (-13 °F)	Storage Temperature Max	70 °C (158 °F)
Protection Against Drop(fall)	1 meter	RX audio SPL(XXdB; X,X W; X,X m)	90dB/0.5W/0.2m
TX Audio, Microphone Sensitivity(XXdB +/-XdB)	-39dB +/-2dB	Microphone Type	Omnidirectional
Headset Connector	QR4+1 female	Battery Life Time	No Battery
Connectivity	Wired	Cable Type	Coiled
Use Voltage	3.0..10.0VDC(0VDC for dynamic microphone)	Electro Magnetic Compatibility (EMC)	EN
Emergency Button	Yes	Attachment/Fastening	Clothing Clip